



**MULTITECH 8**



**ROTEC**  
INTERNATIONAL  
www.rottechbeds.com

MULTITECH 8

**MULTITECH 8**



**SPECIFICATIONS**

- Load capacity: 264 kg (580 lbs)
- Bed weight: 111 kg (245 lbs)
- Minimum height: 21.6 cm (8.5 in.) - Maximum height: 73.7 cm (29 in.)
- Maximum backrest angle: 68 degrees - Maximum footrest angle: 34 degrees
- Bedspring dimensions: 88.9 cm (35 in.) x 198.1 cm (78 in.)
- Overall external dimensions (with sides, half-section): 102.5 cm (41 in.) x 229.6 cm (90 3/8 in.)
- Recommended mattress height: 12.7 cm (5 in.)
- Support for trapeze bar included
- Trendelenburg position available

**FEATURES**

- Whisper-quiet direct-current linear motor
- IP34-approved electrical components protected from dust and water infiltration
- 6 receptacles for IV holder stems
- Battery ensuring temporary autonomous operation
- Casters equipped with a central brake system (synchronized) (2 x 2 casters)
- Possibility of moving the bed even when in its lowest height position
- Metal surfaces covered with electrostatic powder paint
- Selectable, manually adjustable foot angle (choice of three positions: flexion, standard and extension)
- Bed may be separated into two sections for easier transport
- Headboard and footboard bumpers
- Reduced-height bed designed to minimize the possibility of falling
- Bed with the highest load capacity in its category
- Authentic Canadian product

**OPTIONS**

- Rotating half-length bed sides
- Cast composite or wood headboard and footboard
- Trapeze bar (which follows the bed motions when adjusting in height)
- Nurse control
- Transportation dolly

**APPROVALS**

- CSA Canada & USA - File No. 1608300
- Standards: C22.2 No. 0M91 C22.2 No. 601.1 Amendment 2
- C22.2 No. 601.1 M90 C22.2 No. 60601-2-38-03
- C22.2 No. 601.151 94 UL No. 60601-1

- Rotec International holds medical instrument manufacturing licenses issued by Health Canada and the FDA.  
\*Photos and specifications may change without prior notice.